

data sheet

WK-MOD

CONTROL MODULE FOR RAKO WIRED SYSTEMS



WHAT IS IT?

A hard wired push button control module that accommodates up to 12 backlit push buttons. Standard button configurations are shown overleaf with their corresponding part numbers.

Hand finished metal surrounds are available in a number of finishes and should be ordered separately;

Satin Chrome: HS-MOD-SC

Polished Chrome: HS-MOD-PC

Antique Brass: HS-MOD-AB

Polished Brass: HS-MOD-PB

Matt Bronze: HS-MOD-BM
Matt White: HS-MOD-WH

Matt Black: HS-MOD-MB

The WK-MOD-xxx-x connects to the Rako wired network preconfigured to give basic control as defined by the button layout purchased.

The keypad opposite shows:

WK-MOD-110-B with HS-MOD-BM surround.

Product code Key:

WK-MOD	XXX	X
Product	Button	Button
prefix code	Layout	colour
WK-MOD	070	B (Black)
	110	or
	020 etc. see	W (White)
	overleaf for	
	full range	

Wired push button wall plate with up to 12 push buttons. Customisable and programmable via RASOFT Pro



SIMPLE, FLEXIBLE CONTROL

The WK-MOD-xxx-x uses three different button sizes across a range of keypad layouts. This offers a truly flexible range of designs to suit all your lighting control requirements including: Curtain, Blind, Audio, Multi and Single Room layouts.

A WK-HUB and Rasoft Pro programming software is required for setup and configuration of the WK-MOD-xxx-x. Once addressed it is possible to control any Room/Channel in the system, sending commands to each including:

- Scene selection
- Scene toggle
- Level toggle
- Room/Channel raise & lower
- Macro start/stop/control
- House Master controls

Laser etched buttons are backlit with fully programmable blue LEDs.

Designed for use with standard UK single gang back box. Easy connection to the Rako wired CAT5 network is by a removable 8 way Krone punch down module. This can be installed at first fix stage prior to the push button front control module. This protects the control module from being damaged while building works are being finished



data sheet

WK-MOD

ONTROL MODULE FOR RAKO WIRED SYSTEMS



technical data		
dimensions	Control Panel: 86x86x35mm Surround: 88x88x6mm	
fixing	Flush mounting into standard UK single gang back box, minimum depth:35mm	
input supply	15V DC from Rako wired system	
weight	115g	
climate range	Temperature +2C to +40C Humidity +5% to 95% non condensing.	
cable type	UTP CAT5e or CAT6	
terminal type	8 way Krone punch down (screw terminal available by special arrangement)	
communication	Wired Network: CAN	
memory	Flash memory (non volatile) Firmware upgrades via RASOFT Pro	

35mm 86mm

mechanical data



Standard button configurations & part numbers

Emissions - EN61000-6-3 : 2007 Immunity - EN61000-6-1: 2007

Scene 1	Scene 3
Scene 2	Scene 4
Off	٨
	v

Scene 1	Scene 3
Scene 2	Scene 4
Off	On
	Off

WK-MOD-072

Scene 1	Scene 5
Scene 2	Scene 6
Scene 3	Scene 7
Scene 4	Scene 8
Off	۸
	٧

Scene 1	Scene 1
Scene 2	Scene 2
Scene 3	Scene 3
Scene 4	Scene 4
Off	Off

Scene 1	Open
Scene 2	•
Scene 3	Close
Scene 4	
Off	٨
	٧

1	5
2	6
3	7
4	8
All	Open
	Close

WK-MOD-070

On	٨
Off	v
WK-MOD-040	

On	On
Off	Off

WK-MOD-041

WK-MOD-110			
On			
Off			
WK-MOD-020			

WK-MOD-060

WK-MOD-103

WK-MOD-030

WK-MOD-101

WK-MOD-111